(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 July 2005 (14.07.2005)

PCT

(10) International Publication Number WO 2005/064759 A1

(51) International Patent Classification⁷:

H02H 7/045

(21) International Application Number:

PCT/SE2004/001997

(22) International Filing Date:

22 December 2004 (22.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0303615-9

31 December 2003 (31.12.2003) SE

(71) Applicant (for all designated States except US): ABB AB [SE/SE]; Kopparbergsvägen 2, S-721 83 Västeras (SE).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): GAJIC, Zoran [SE/SE]; Regementsgatan 59, S-723 45 Västerås (SE). BRNCIC, Ivo [SE/SE]; Fårövägen 4, S-722 44 Västerås (SE).
- (74) Agent: ABB AB; Legal & Compliance/Intellectual Property, Forskargrand 8, S-721 78 VASTERAS (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FO RFAULT DETECTION IN TRANSFORMERS OR POWER LINES



(57) Abstract: The invention refers to method for fault detection in a power transformer/autotransformer and/or interconnected power lines, which are within the zone protected by the differential protection, and particularly suitable for detecting turn-to-turn faults in power transformer/autotransformer windings. The method according to the invention is achieved by measuring all individual instantaneous phase currents of the protected object, calculating individual phase currents as fundamental frequency phasors, calculating the contributions of the individual protected object sides negative sequence currents to the total negative sequence differential current by compensating for the phase shift of an eventual power transformer within the protected zone, comparing the relative positions of the compensated individual sides negative sequence currents in the complex plane, in order to determine whether the source of the negative sequence currents, i.e. the fault position, is within the protected zone or outside of the protected zone, delimited with current transformer locations, disconnecting the protected object if determined that the source of the negative sequence currents is within the protected zone.



